

## **SATO-Direct 100P**

FACESHEET	40	
Basis Weight (lb/ream)	49	
Caliper Target (mils)	3.2	Film
Tensile MD Target (Ib/in)	25	
Tensile CD Target (Ib/in)	16	PRODUCT TYPE
Tear MD (grams)		
Tear CD (grams)		Tag
Stiffness MD (grams)		Receipt
Stiffness CD (grams)		
Color	White	IMAGING CAPABILITY
		✓ Direct Thermal
ADHESIVE		Thermal Transfer - Wax
Description	Permanent	Thermal Transfer - Wax/Resin
		Thermal Transfer - Resin
Caliper Target (mils)	0.6	Laser
LINER		AGENCY RECOGNITION
Description	40# White Kraft	UL
Caliper Target (mils)	2.4	CUL
		FSC
TOTAL CALIPER		FDA.21 CFR 175.105
Caliper Target (mils)	6.2	✓ BPA Free
ENVIRONMENT		MAXIMUM OUTDOOR LIFE
Storage Temperature (°F)	40 to 72	✓ For Indoor Use only
Storage Humidity (%RH)	35 to 75	<6 months
Shelf Life (months)	12	<12 months
Min Application Temp (°F)	32	<12 months
Service Temperature (°F)	-4 to 120	2 years
	-// ///	
	4 10 120	
SPECIAL NOTES:	4 10 120	

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

## SATO AMERICA CORPORATE 14125 South Bridge Circle

Charlotte, NC 28273 Phone: (704) 644-1650 sales-sal@sato-global.com

## LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA CANADA CARIBBEAN

## www.satoamerica.com

©2021 SATO America . All rights Reserved. • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

9007027