



**ZEBRA**

SUGGESTED APPLICATIONS

# Z-Slip

## FEATURES

- Patented direct thermal, paper and polypropylene label combination
- Excellent print quality
- Unique construction protects printable side from chemicals and keeps information secure
- Available in white (65091RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth coated direct thermal paper	5.9 mil
Adhesive	All-temp, acrylic-based	0.9 mil
Liner	Clear polypropylene	2.1 mil
<b>TOTAL ± 10%</b>		<b>8.9 mil</b>

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
23° F (-5° C)	-20° F to 131° F (-29° C to 55° C)	72° F (22° C) at 50% RH

- Shipping applications



## Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

	Chemical	Direct Thermal
Weak	Blood	●
	Body Fluid	●
	Salt Water	●
	Water	●
	Window Cleaner	●
Moderate	Alcohol	●
	Ammonia	●
	Bleach	●
	IPA	●
Harsh	Gasoline	●
	Grease	●
	Oil	●
Extreme	Acetone	●
	IR Reflow	●
	MEK	●
	TCE	●
	Xylene	●

● Recommended ● Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.